## QAV-PRO LIFTER

PROFESSIONAL EQUIPMENT FOR CINEMATIC FPV







## TABLE OF CONTENTS

SECTION # 1 ARMS ASSEMBLY

SECTION # 2 BODY ASSEMBLY

SECTION # 3 ISOLATION SYSTEM ASSEMBLY

SECTION # 4 MISCELANEOUS PARTS AND FINAL DETAILS








SECTION #1


ARMS ASSEMBLY





















## PARTS NEEDED FOR THIS ASSEMBLY

## **BODY ASSEMBLY**



MOUNT

 $M3 \times 12$ MM


**SCREWS** 


TO MOUNT THE WIRE GUARD TO THE REAR OF

THE BOTTOM PLATE ASSEMBLY, THEN DO THE

SAME WITH THE M3x12MM COUNTERSUNK

SCREWS FOR THE USB EXTENSION MOUNT.





ADDITIONAL PARTS
INCLUDED



M3x22mm STACK SCREWS



M3 STACK
SILICONE O-RINGS







M3 STACK NYLON NUTS




M1.6x10mm DJI AIR UNIT SCREWS













 PEEL THE PAPER FROM THE ADHESIVE BACKING ON EACH LIPO PAD SEGMENT AND STICK THEM INSIDE THE ENGRAVED POCKETS.

**2.** SEPARATE THE ALPHA GEL AND INSTALL HALVES AS SHOWN, INSERTING THE BRASS COLLAR AFTER THE GEL IS IN PLACE.





**6.** PLACE A CARBON WASHER ON EACH EXPOSED SCREW ON THE TOP PLATE OF THE BASE ASSEMBLY, THEN ALIGN THE BRASS COLLARS IN THE ALPHA GEL WITH EACH EXPOSED SCREW AND GENTLY PUSH DOWN UNTIL THE ISOLATION ASSEMBLY IS SITTING EVEN. PLACE THE SECOND CARBON WASHER ON TOP, THEN TIGHTEN DOWN THE THUMB NUTS UNTIL THEY ARE SECURE.



